

STREET LIGHTING

LUMINAIRE

CPY SERIES



APPLICATIONS

- Highways
- Street and Roads
- Industrial Fields
- Residential Areas
- Parks
- Perimeter and Security Lighting
- Cross Roads
- Car Parks

FEATURES

- Ergonomic Body
- Suitable for Led and Energy Saving Lamps
- Open from Bottom
- Tool Free Opening System



| Power W | Lamp Type | Current A | Luminaire Lamp Type | Figure | a mm | b mm | c mm | Lamp Holder Type | Pole Mount Consale | Weight kg | Capacitor mf | Quality Certificates |
|------------|-----------|-----------|---------------------|--------|------|------|------|------------------|--------------------|-----------|--------------|----------------------|
| 220V, 50Hz | | | | | | | | | | | | |
| | | | CPY E-40 | 2 | 340 | 695 | 262 | E-40 | φ42- φ60 | 6,000 | | CE |
| 150 | SV | 1,80 | CPY150 | 2 | 340 | 695 | 262 | E-40 | φ42- φ60 | 8,904 | 20 | CE |
| 210 | SV | 2,15 | CPY 210 | 2 | 340 | 695 | 262 | E-40 | φ42- φ60 | 10,000 | 20 | CE |
| 250 | HG | 2,15 | CPY 250 | 2 | 340 | 695 | 262 | E-40 | φ42- φ60 | 10,000 | 20 | CE |
| 250 | SV | 3,00 | CPY 250 | 2 | 340 | 695 | 262 | E-40 | φ42- φ60 | 11,000 | 32 | CE |
| 400 | HG | 3,15 | CPY 400 | 2 | 340 | 695 | 262 | E-40 | φ42- φ60 | 11,000 | 32 | CE |
| 400 | MH | 3,50 | CPY 400 | 2 | 340 | 695 | 262 | E-40 | φ42- φ60 | 11,688 | 35 | CE |
| 400 | SV | 4,60 | CPY 400 | 2 | 340 | 695 | 262 | E-40 | φ42- φ60 | 11,789 | 45 | CE |
| 230V, 50Hz | | | | | | | | | | | | |
| 150 | SV | 1,80 | CPY150 | 2 | 340 | 695 | 262 | E-40 | φ42- φ60 | 8,930 | 20 | CE |
| 210 | SV | 2,15 | CPY 210 | 2 | 340 | 695 | 262 | E-40 | φ42- φ60 | 10,434 | 20 | CE |
| 250 | HG | 2,15 | CPY 250 | 2 | 340 | 695 | 262 | E-40 | φ42- φ60 | 10,434 | 20 | CE |
| 250 | SV | 3,00 | CPY 250 | 2 | 340 | 695 | 262 | E-40 | φ42- φ60 | 11,035 | 32 | CE |
| 400 | HG | 3,15 | CPY 400 | 2 | 340 | 695 | 262 | E-40 | φ42- φ60 | 11,038 | 32 | CE |
| 400 | MH | 3,50 | CPY 400 | 2 | 340 | 695 | 262 | E-40 | φ42- φ60 | 11,745 | 35 | CE |
| 400 | SV | 4,60 | CPY 400 | 2 | 340 | 695 | 262 | E-40 | φ42- φ60 | 11,836 | 45 | CE |

Terminal Blocks: 1,5 - 2,5 mm² / Luminaire Class 2 / TS EN 60598-1 TS EN 60598-2-3

Option: Monoblock Reflector and Gear Plate

Seal Type : Resistant To Heat Silicon

Diffuser : Polycarbon

Power Factor : 0,95 - 1

Body Type : Polymer / GRP, IK 08

Box Dimension : 695mmx340mmx265mm

LIGHT DISTRUBUTION CURVES

