

STREET LIGHTING

LUMINAIRE

CP
SERIES



APPLICATIONS

- Highways
- Street and Roads
- Industrial Fields
- Residential Areas
- Parks
- Perimeter and Security Lighting
- Cross Roads
- Car Parks

FEATURES

- Ergonomic Body
- Monoblock Anodized High Purity Aluminium Reflector
- Diffuser Part Open from Botton, Gear Part Open from Top System
- Removable Ballast Kit
- Tool Free Opening System

IP65





Power W	Lamp Type	Current A	Luminaire Lamp Type	Figure	a mm	b mm	c mm	Lamp Holder Type	Pole Mount Consale	Weight kg	Capacitor mf	IP	Quality Certificates
220V - 230V, 50Hz													
			CPE-40	2	715	335	285	E-40	φ42- φ60	7,800			TSE/CE
150	SV	1,80	CP 150	2	715	335	285	E-40	φ42- φ60	9,904	20	65	TSE/CE
210	SV	2,15	CP 210	2	715	335	285	E-40	φ42- φ60	10,204	20	65	TSE/CE
250	HG	2,15	CP 250	2	715	335	285	E-40	φ42- φ60	10,204	20	65	TSE/CE
250	SV	3,00	CP 250	2	715	335	285	E-40	φ42- φ60	10,930	32	65	TSE/CE
400	HG	3,15	CP 400	2	715	335	285	E-40	φ42- φ60	11,452	32	65	TSE/CE
400	MH	3,50	CP 400	2	715	335	285	E-40	φ42- φ60	11,653	35	65	TSE/CE
400	SV	4,60	CP 400	2	715	335	285	E-40	φ42- φ60	11,760	45	65	TSE/CE

Option : Flat Reflector
 Seal Type : Resistant To Heat Silicon
 Diffuser : Polycarbon
 Power Factor : 0,95 - 1
 Body Type : Polymer / GRP, IK 08
 Box Dimension : 720mmx334mmx275mm

LIGHT DISTRUBTION CURVES

