



CSY 400

Specifications


| | |
|------------------------------|-----------------------------|
| Nominal Power (W) | 400 W |
| Luminous Flux (lm) | 28000 - 40000 lumen |
| Efficacy (lm/W) | 70 - 100 lm/W |
| Nominal Voltage (V) | 220 - 240 V / 50 - 60 Hz |
| Ingress Protection | IP 65 |
| Impact Protection | IK 08 |
| Lamp Holder | E40 |
| IEC Protection Class | Class I |
| Colour Temperature (K) | 2000 K |
| Colour Rendering Index (CRI) | > 25 |
| Operating Temperature (Ta) | Outdoor -20 °C / +50 °C |
| Diffuser | 4 mm Tempered Glass |
| Optic | Aluminum Reflector |
| Housing | Polymer |
| Mounting Part | Die-Cast Aluminum |
| Mounting Diameters | Ø42 mm - Ø60 mm |
| Tilt Angle | -15° / +15° |
| Dimensions and Weight | 700 x 330 x 180 mm / 8.8 kg |



Description

Street Lighting Luminaire

Photometric Distribution:



Complied Standards:

Approved by Turkish General Directorate of Highways
EN 60598-1:2015+A1:2018
EN 60598-2-13:2006+A1:2012+A2:2016
EN 62262:2002
IEC TR 62778:2014

Applications

- Streets and Roads
- Parks and Car Lots
- Residential Areas
- Industrial Zones
- Railway Stations



CORPORATE

Company
Quality and R&D
Certificates
News
Career

PRODUCTS

Road and Street Luminaires
Floodlights and Area Luminaires
Industrial and Tunnel Luminaires
Indoor and Office Luminaires
Poles and Bollards
IMAJ® Ballasts and Igniters
GRITCON® Smart Control
GRITSOL® Solar Systems

CONTACT US

E-Mail : sales@grupimaj.com
Phone : +90 212 689 93 08-09-10 (pbx)
Fax : +90 212 689 93 11
GSM : +90 507 699 53 32
Address : Kavaklı district, Deniz Aktaş street, No: 6 |
345520 Beylikdüzü / Istanbul / Turkey

