

STREET LIGHTING

LUMINAIRE

CSY SERIES



APPLICATIONS

- Highways
- Street and Roads
- Industrial Fields
- Residential Areas
- Parks
- Perimeter and Security Lighting
- Cross Roads
- Car Parks

FEATURES

- Ergonomic Body
- Suitable for Led and Energy Saving Lamps
- Open from Bottom
- Tool Free Opening System



Power W	Lamp Type	Current A	Luminaire Lamp Type	Figure	a mm	b mm	c mm	Lamp Holder Type	Pole Mount Consale	Weight kg	Capacitor mf	IP	Quality Certificates
220V, 50Hz													
			CSY E-40	1	695	340	185	E-40	φ42- φ60	6,000		54	CE
150	SV	1,80	CSY 150	1	695	340	185	E-40	φ42- φ60	8,904	20	54	CE
210	SV	2,15	CSY 210	1	695	340	185	E-40	φ42- φ60	10,000	20	54	CE
250	HG	2,15	CSY 250	1	695	340	185	E-40	φ42- φ60	10,000	20	54	CE
250	SV	3,00	CSY 250	1	695	340	185	E-40	φ42- φ60	11,000	32	54	CE
400	HG	3,15	CSY 400	1	695	340	185	E-40	φ42- φ60	11,000	32	54	CE
400	MH	3,50	CSY 400	1	695	340	185	E-40	φ42- φ60	11,688	35	54	CE
400	SV	4,60	CSY 400	1	695	340	185	E-40	φ42- φ60	11,789	45	54	CE
230V, 50Hz													
150	SV	1,80	CSY 150	1	695	340	185	E-40	φ42- φ60	8,930	20	54	CE
210	SV	2,15	CSY 210	1	695	340	185	E-40	φ42- φ60	10,434	20	54	CE
250	HG	2,15	CSY 250	1	695	340	185	E-40	φ42- φ60	10,434	20	54	CE
250	SV	3,00	CSY 250	1	695	340	185	E-40	φ42- φ60	11,035	32	54	CE
400	HG	3,15	CSY 400	1	695	340	185	E-40	φ42- φ60	11,038	32	54	CE
400	MH	3,50	CSY 400	1	695	340	185	E-40	φ42- φ60	11,745	35	54	CE
400	SV	4,60	CSY 400	1	695	340	185	E-40	φ42- φ60	11,836	45	54	CE

Terminal Blocks: 1,5 - 2,5 mm² / Luminaire Class 2 / TS EN 60598-1 TS EN 60598-2-3

- Option : Monoblock Reflector and Gear Plate
- Seal Type : Resistant To Heat Silicon
- Diffuser : Tempered Flat Glass
- Power Factor : 0,95 - 1
- Body Type : Polymer / GRP, IK 08
- Box Dimension : 685mmx324mmx185mm

LIGHT DISTRUBUTION CURVES

