



GATEWAY

Specifications

Nominal Voltage (V)	24 Vdc
Power Consumption (W)	< 2 W
Current Absorption	72 mA
Clock	Astronomic. RTC
Operating Conditions	-30 °C / +75 °C
Ingress Protection	IP 20
Impact Protection	IK 06
LED	RGB
Serial Interfaces	2 RS485 Ports
USB Ports	Type A OTG Port / Type B Port
Ethernet	RJ45 Connector
Operating System	Linux Yocto
Processor	Single-Core Cortex A7
RAM Memory	128 MB DDR3-800
Flash Memory	256 MB NAND
SD Card	Micro SDHC - 32 GB
Dimensions	113.3 x 18.9 x 77 mm

IP20 IK06 CE

Description

IoT Gateway

Applications

- Streets and Roads
- Parks and Car Lots
- Indoors
- Tunnels
- Public Transport and Traffic
- Air, Public Green and Waste Management
- Individual Monitoring and Presence Management
- Gas Metering and Detecting



CORPORATE

Company
Quality and R&D
Certificates
News
Career

PRODUCTS

Road and Street Luminaires
Floodlights and Area Luminaires
Industrial and Tunnel Luminaires
Indoor and Office Luminaires
Poles and Bollards
IMAJ® Ballasts and Ignitors
GRITCON® Smart Control
GRITSOL® Solar Systems

CONTACT US

E-Mail : sales@grupimaj.com
Phone : +90 212 689 93 08-09-10 (pbx)
Fax : +90 212 689 93 11
GSM : +90 507 699 53 32
Address : Kavaklı district, Deniz Aktaş street, No: 6 |
345520 Beylikdüzü / İstanbul / TÜRKİYE