



## HAWK MIDI 75

### Specifications


Nominal Power (W)	75 W
Luminous Flux (lm)	8625 - 10125 lumen
Efficacy (lm/W)	115 - 135 lm/W
Nominal Voltage (V)	220 - 240 V / 50 - 60 Hz
Power Factor	> 0.95
IEC Protection Class	Class I
Ingress Protection	IP 67
Impact Protection	IK 09
Colour Rendering Index (CRI)	> 70
Colour Temperature (K)	2700 - 6500 K
Operating Temperature (Ta)	Outdoor -20 °C / +50 °C
Diffuser	PMMA
Optic	PMMA
Surge Protection (kV)	6 - 10 kV
Control Protocols	1-10V DALI ZigBee DMX
Housing	Aluminum
Tilt Angle	-90° / +90°
Dimensions and Weight	301 x 185 x 74 mm / 3,2 kg
Colour Options	All RAL colours



### Description

LED Industrial and Tunnel Lighting Luminaire

#### Photometric Distribution:



#### Complied Standards:

LM 79-08, LM 80  
 EN 60598-1:2015+A1:2018  
 EN 60598-2-13:2006+A1:2012+A2:2016  
 EN 62262:2002  
 IEC TR 62778:2014

#### LED Lifetime:

60,000 hours L80  
 100,000 hours L70

### Applications

- Tunnel and Underpass
- Industrial Zones
- Parks and Car Lots
- Architectural and Urban
- Railway Stations

