

LED FLOODLIGHT

HAWK
SERIES



APPLICATIONS

- Sports Areas
- Parks and Car parks
- Residential Areas
- Industrial Areas
- Port Lighting
- Factory Lighting
- Architectural Lighting

FEATURES

- Entirely domestic manufacturing except for Led and drivers
- Long life due to thermal design cooling block
- IP66 rating
- Manufacturing complying with TS EN 60598-2-5



HAWK LED FLOODLIGHT

| | POWER | | Lumious Flux (LM) | | Color Temperature | CRI |
|---------|-------|------|-------------------|-------|--|----------|
| | Min. | Max. | Min. | Max. | | |
| 12 LED | 30W | 40W | 3600 | 4400 | 3000K- 4000K- 5000K- 6000K- 6500K- | CRI > 70 |
| 24 LED | 60W | 80W | 7200 | 8800 | | |
| 36 LED | 90W | 120W | 10800 | 13200 | | |
| 48 LED | 120W | 160W | 14400 | 17600 | | |
| 60 LED | 150W | 200W | 18000 | 22000 | | |
| 72 LED | 180W | 240W | 21600 | 26400 | | |
| 84 LED | 210W | 280W | 25200 | 30800 | | |
| 96 LED | 240W | 320W | 28800 | 35200 | | |
| 108 LED | 270W | 360W | 32400 | 39600 | | |
| 120 LED | 300W | 400W | 36000 | 44000 | | |



"LIGHTNING THE BIGGEST AIRPORT CONSTRUCTION AREA OF THE WORLD" - "ISTANBUL GRAND AIRPORT"

LIGHT DISTRIBUTION CURVES

