



HG250 - 250

Specifications

Lamp Power (W)	250 W
Lamp Type	HID
Nominal Voltage (V)	220 - 230 V / 50 Hz
Current (A)	2,15 A
Cos Φ	0,57
Loading Capacitance	20 μ F
IEC Protection Class	Class I
Thermal Protection	Yes
Operating Temperature (Ta)	70 °C
Dimensions and Weight	136 x 69 x 59 mm / 1,905 kg
Terminal Blocks	1,5 - 2,5 mm ²
Box Quantity	12 Pieces



Description

Standart HID Ballast:

Complied Standards:

TS EN 60923

TS EN 61347

Applications

- High Pressure Mercury Lamp Ballasts



CORPORATE

Company
Quality and R&D
Certificates
News
Career

PRODUCTS

Road and Street Luminaires
Floodlights and Area Luminaires
Industrial and Tunnel Luminaires
Indoor and Office Luminaires
Poles and Bollards
IMAJ® Ballasts and Ignitors
GRITCON® Smart Control
GRITSOL® Solar Systems

CONTACT US

E-Mail : sales@grupimaj.com
Phone : +90 212 689 93 08-09-10 (pbx)
Fax : +90 212 689 93 11
GSM : +90 507 699 53 32
Address : Kavaklı district, Deniz Aktaş street, No: 6 |
345520 Beylikdüzü / İstanbul / TÜRKİYE

