



IM04 100 - 400

Specifications

| | |
|----------------------------|---------------------------|
| Lamp Power (W) | 100 - 400 W |
| Lamp Type | HPS - HID |
| Nominal Voltage (V) | 220 - 240 V / 50 - 60 Hz |
| Ignition Voltage (V) | 3 - 4,5 kV |
| Current (A) | 4,5 A |
| Loading Capacitance | 20 - 150 pF |
| IEC Protection Class | Class II |
| Operating Temperature (Ta) | -25 °C / + 85 °C |
| Cut of Time | No Timing |
| Dimensions and Weight | 30 x 90 x 33 mm / 122 gr |
| Terminal Blocks | 1,5 - 2,5 mm ² |
| Box Quantity | 50 Pieces |



Description

Timed Imposed and Standard Pulse Ignitors

Complied Standards:

TS EN 60927

TS EN 61347-2-1

Applications

- High Pressure Sodium Vapour Lamps
- Metal Halide Lamps



CORPORATE

Company
Quality and R&D
Certificates
News
Career

PRODUCTS

Road and Street Luminaires
Floodlights and Area Luminaires
Industrial and Tunnel Luminaires
Indoor and Office Luminaires
Poles and Bollards
IMAJ® Ballasts and Ignitors
GRITCON® Smart Control
GRITSOL® Solar Systems

CONTACT US

E-Mail : sales@grupimaj.com
Phone : +90 212 689 93 08-09-10 (pbx)
Fax : +90 212 689 93 11
GSM : +90 507 699 53 32
Address : Kavaklı district, Deniz Aktaş street, No: 6 |
345520 Beylikdüzü / Istanbul / Turkey

