

STREET LIGHTING

LUMINAIRE

MS
SERIES



APPLICATIONS

- Street and Roads
- Industrial Fields
- Residential Areas
- Parks
- Perimeter and Security Lighting
- Car Parks

FEATURES

- Ergonomic Body
- Tool Free Bowl Removal with Hinged System
- Open from Bottom
- Flat Reflector
- Suitable for Energy Saving Lamps

IP65



Power W	Lamp Type	Current A	Luminaire Lamp Type	Figure	a mm	b mm	c mm	Lamp Holder Type	Pole Mount Consale	Weight kg	Capacitor mf	IP	Quality Certificates
220V, 50Hz													
			MS E-27	1	560	280	138	E-27	φ42	3,300		65	TSE/CE
			MS E-40	1	560	280	138	E-40	φ42	3,300		65	TSE/CE
50	SV	0,76	MS 50	1	560	280	138	E-27	φ42	4,800	10	65	TSE/CE
70	SV	1,00	MS 70	1	560	280	138	E-27	φ42	4,800	12	65	TSE/CE
100	SV	1,20	MS 100	1	560	280	138	E-40	φ42	5,000	14	65	TSE/CE
110	SV	1,15	MS 110	1	560	280	138	E-27	φ42	4,700	10	65	TSE/CE
125	HG	1,15	MS 125	1	560	280	138	E-27	φ42	4,700	10	65	TSE/CE
230V, 50Hz													
50	SV	0,76	MS 50	1	560	280	138	E-27	φ42	4,812	10	65	TSE/CE
70	SV	1,00	MS 70	1	560	280	138	E-27	φ42	4,819	12	65	TSE/CE
100	SV	1,20	MS 100	1	560	280	138	E-40	φ42	5,025	14	65	TSE/CE
110	SV	1,15	MS 110	1	560	280	138	E-27	φ42	4,716	10	65	TSE/CE
125	HG	1,15	MS 125	1	560	280	138	E-27	φ42	4,716	10	65	TSE/CE

Seal Type : Resistant To Heat Silicon
 Diffuser : Tempered Flat Glass
 Power Factor : 0,95 - 1
 Body Type : Polymer / GRP, IK 08
 Box Dimension : 560mmx280mmx140mm

LIGHT DISTRUBUTION CURVES

