


PS 150**Specifications**

Nominal Power (W)	150 W
Luminous Flux (lm)	10500 - 15000 lumen
Efficacy (lm/W)	70 - 100 lm/W
Nominal Voltage (V)	220 - 240 V / 50 - 60 Hz
IEC Protection Class	Class I
Lamp Holder	E40
Ingress Protection	IP 65
Impact Protection	IK 08
Colour Rendering Index (CRI)	> 25
Colour Temperature (K)	2000 K
Operating Temperature (Ta)	Outdoor -20 °C / +50 °C
Diffuser	4 mm Tempered Glass
Optic	Aluminum Reflector
Housing	Polymer
Mounting Part	Die-Cast Aluminum
Tilt Angle	-90° / +90°
Dimensions and Weight	550 x 426 x 165 mm / 4 kg

IK08    **IP65** 
Description

Floodlight

Photometric Distribution:*Complied Standards:*
 LM 79-08, LM 80
 EN 60598-1:2015+A1:2018
 EN 60598-2-13:2006+A1:2012+A2:2016
 EN 62262:2002
 IEC TR 62778:2014
Applications

- Industrial Zones
- Sports Venues
- Parks and Car Lots
- Architectural and Urban
- Bridges and Viaducts
- Residential Areas
- Railway Stations

