



TPY 70

Specifications


Nominal Power (W)	70 W
Luminous Flux (lm)	4900 - 7000 lumen
Efficacy (lm/W)	70 - 100 lm/W
Nominal Voltage (V)	220 - 240 V / 50 - 60 Hz
Ingress Protection	IP 65
Impact Protection	IK 08
Lamp Holder	E27
IEC Protection Class	Class I
Colour Temperature (K)	2000 K
Colour Rendering Index (CRI)	> 25
Operating Temperature (Ta)	Outdoor -20 °C / +50 °C
Diffuser	Polycarbon
Optic	Aluminum Reflector
Housing	Polymer
Mounting Part	Die-Cast Aluminum
Mounting Diameters	Ø42 mm - Ø60 mm
Tilt Angle	-15° / +15°
Dimensions and Weight	564 x 250 x 172 mm / 3.3 kg



Description

Street Lighting Luminaire

Photometric Distribution:



Complied Standards:

Approved by Turkish General Directorate of Highways
EN 60598-1:2015+A1:2018
EN 60598-2-13:2006+A1:2012+A2:2016
EN 62262:2002
IEC TR 62778:2014

Applications

- Streets and Roads
- Parks and Car Lots
- Residential Areas
- Industrial Zones
- Railway Stations



CORPORATE

Company
Quality and R&D
Certificates
News
Career

PRODUCTS

Road and Street Luminaires
Floodlights and Area Luminaires
Industrial and Tunnel Luminaires
Indoor and Office Luminaires
Poles and Bollards
İMAJ® Ballasts and Ignitors
GRITCON® Smart Control
GRITSOL® Solar Systems

CONTACT US

E-Mail : sales@grupimaj.com
Phone : +90 212 689 93 08-09-10 (pbx)
Fax : +90 212 689 93 11
GSM : +90 507 699 53 32
Address : Kavaklı district, Deniz Aktaş street, No: 6 |
345520 Beylikdüzü / İstanbul / Turkey