

STREET LIGHTING

LUMINAIRE

TP
SERIES



APPLICATIONS

- Highways
- Street and Roads
- Industrial Fields
- Residential Areas
- Parks
- Perimeter and Security Lighting
- Cross Roads
- Car Parks

FEATURES

- Ergonomic Body
- Monoblock Anodized High Purity Aluminium Reflector
- Open from Top
- Removable Ballast Kit
- Low Maintenance Cost
- Tool Free Opening System



Power W	Lamp Type	Current A	Luminaire Lamp Type	Figure	a mm	b mm	c mm	Lamp Holder Type	Pole Mount Consale	Weight kg	Capacitor mf	IP	Quality Certificates
220V, 50Hz													
			TP E-27	2	658	320	200	E-27	φ42- φ60	3,000		65	TSE/CE
			TP E-40	2	658	320	200	E-40	φ42- φ60	3,010		65	TSE/CE
50	SV	0,76	TP 50	2	658	320	200	E-27	φ42- φ60	6,000	10	65	TSE/CE
70	SV	1,00	TP 70	2	658	320	200	E-27	φ42- φ60	6,000	12	65	TSE/CE
100	SV	1,15	TP 100	2	658	320	200	E-40	φ42- φ60	6,500	14	65	TSE/CE
110	SV	1,15	TP 110	2	658	320	200	E-27	φ42- φ60	6,000	10	65	TSE/CE
125	HG	1,15	TP 125	2	658	320	200	E-27	φ42- φ60	6,000	10	65	TSE/CE
150	SV	1,80	TP 150	2	658	320	200	E-40	φ42- φ60	7,000	20	65	TSE/CE
210	SV	2,15	TP 210	2	658	320	200	E-40	φ42- φ60	7,500	20	65	TSE/CE
250	HG	2,15	TP 250	2	658	320	200	E-40	φ42- φ60	7,500	20	65	TSE/CE
230V, 50Hz													
50	SV	0,76	TP 50	2	658	320	200	E-27	φ42- φ60	6,010	10	65	TSE/CE
70	SV	1,00	TP 70	2	658	320	200	E-27	φ42- φ60	6,010	12	65	TSE/CE
100	SV	1,15	TP 100	2	658	320	200	E-40	φ42- φ60	6,530	14	65	TSE/CE
110	SV	1,15	TP 110	2	658	320	200	E-27	φ42- φ60	6,010	10	65	TSE/CE
125	HG	1,15	TP 125	2	658	320	200	E-27	φ42- φ60	6,010	10	65	TSE/CE
150	SV	1,80	TP 150	2	658	320	200	E-40	φ42- φ60	7,100	20	65	TSE/CE
210	SV	2,15	TP 210	2	658	320	200	E-40	φ42- φ60	7,600	20	65	TSE/CE
250	HG	2,15	TP 250	2	658	320	200	E-40	φ42- φ60	7,600	20	65	TSE/CE

Terminal Blocks: 1,5 - 2,5 mm² / Luminaire Class 1 / TS EN 60598-1 TS EN 60598-2-3

Seal Type : Resistant To Heat Silicon
 Diffuser : Polycarbon
 Power Factor : 0,95 - 1
 Body Type : Polymer / GRP, IK 08
 Box Dimension : 670mmx320mmx208mm

LIGHT DISTRUBTION CURVES

