

# STREET LIGHTING

## LUMINAIRE

# TS

SERIES



### APPLICATIONS

- Highways
- Street and Roads
- Industrial Fields
- Residential Areas
- Parks
- Perimeter and Security Lighting
- Cross Roads
- Car Parks

### FEATURES

- Open from Top
- Monoblock Anodized High Purity Aluminium Reflector
- Removable Ballast Kit
- Low Maintenance Cost
- Tool Free Opening System



Power W	Lamp Type	Current A	Luminaire Lamp Type	Figure	a mm	b mm	c mm	Lamp Holder Type	Pole Mount Consale	Weight kg	Capacitor mf	IP	Quality Certificates
220V, 50Hz													
			TS E-27	1	658	320	150	E-27	φ42- φ60	3,000		65	TSE/CE
			TS E-40	1	658	320	150	E-40	φ42- φ60	3,010		65	TSE/CE
50	SV	0,76	TS 50	1	658	320	150	E-27	φ42- φ60	6,000	10	65	TSE/CE
70	SV	1,00	TS 70	1	658	320	150	E-27	φ42- φ60	6,000	12	65	TSE/CE
100	SV	1,15	TS 100	1	658	320	150	E-40	φ42- φ60	6,500	14	65	TSE/CE
110	SV	1,15	TS 110	1	658	320	150	E-27	φ42- φ60	6,000	10	65	TSE/CE
125	HG	1,15	TS 125	1	658	320	150	E-27	φ42- φ60	6,000	10	65	TSE/CE
150	SV	1,80	TS 150	1	658	320	150	E-40	φ42- φ60	7,000	20	65	TSE/CE
210	SV	2,15	TS 210	1	658	320	150	E-40	φ42- φ60	7,500	20	65	TSE/CE
250	HG	2,15	TS 250	1	658	320	150	E-40	φ42- φ60	7,500	20	65	TSE/CE
230V, 50Hz													
50	SV	0,76	TS 50	1	658	320	150	E-27	φ42- φ60	6,010	10	65	TSE/CE
70	SV	1,00	TS 70	1	658	320	150	E-27	φ42- φ60	6,010	12	65	TSE/CE
100	SV	1,15	TS 100	1	658	320	150	E-40	φ42- φ60	6,530	14	65	TSE/CE
110	SV	1,15	TS 110	1	658	320	150	E-27	φ42- φ60	6,010	10	65	TSE/CE
125	HG	1,15	TS 125	1	658	320	150	E-27	φ42- φ60	6,010	10	65	TSE/CE
150	SV	1,80	TS 150	1	658	320	150	E-40	φ42- φ60	7,100	20	65	TSE/CE
210	SV	2,15	TS 210	1	658	320	150	E-40	φ42- φ60	7,600	20	65	TSE/CE
250	HG	2,15	TS 250	1	658	320	150	E-40	φ42- φ60	7,600	20	65	TSE/CE

Terminal Blocks: 15 - 2.5 mm<sup>2</sup> / Luminaire Class 1 / TS EN 60598-1 TS EN 60598-2-3

Seal Type : Resistant To Heat Silicon  
 Diffuser : Tempered Flat Glass  
 Power Factor : 0,95 - 1  
 Body Type : Polymer / GRP, IK 08  
 Box Dimension : 670mmx320mmx160mm

### LIGHT DISTRUBUTION CURVES

