

# FLOODLIGHTS

PS  
SERIES



## APPLICATIONS

- Industrial Fields
- Residential Areas
- Parks
- Perimeter and Security Lighting
- Cross Roads
- Car Parks
- Building Exteriors
- Sports Areas

## FEATURES

- High Efficient Lighting Distribution
- High Purity Anodized Aluminum Reflector
- Optional Symetric and Asymmetric Reflector
- Tool Free Opening System



Power W	Lamp Type	Current A	Luminaire Lamp Type	Figure	a mm	b mm	c mm	Lamp Holder Type	Pole Mount Consale	Weight kg	Capacitor mf	IP	Quality Certificates
220V, 50Hz													
			PS E-40	1	550	425	165	E-40	Bracket	9,500		65	TSE/CE
			PS E-40	1	550	425	165	E-40	Bracket	10,000		66	TSE/CE
150	MH	1,80	PS 150	1	550	425	165	E-40	Bracket	10,200	20	65	CE
250	MH	3,00	PS 250	1	550	425	165	E-40	Bracket	10,300	32	65	TSE/CE
400	MH	3,50	PS 400	1	550	425	165	E-40	Bracket	10,350	35	65	TSE/CE
250	SV	3,00	PS 250	1	550	425	165	E-40	Bracket	10,300	32	65	TSE/CE
400	SV	3,50	PS 400	1	550	425	165	E-40	Bracket	10,500	45	65	TSE/CE
230V, 50Hz													
150	MH	1,80	PS 150	1	550	425	165	E-40	Bracket	10,230	20	65	CE
250	MH	3,00	PS 250	1	550	425	165	E-40	Bracket	10,337	32	65	TSE/CE
400	MH	3,50	PS 400	1	550	425	165	E-40	Bracket	10,380	35	65	TSE/CE
250	SV	3,00	PS 250	1	550	425	165	E-40	Bracket	10,337	32	65	TSE/CE
400	SV	3,50	PS 400	1	550	425	165	E-40	Bracket	10,550	45	65	TSE/CE

Terminal Blocks: 15 - 2.5 mm<sup>2</sup> / Luminaire Class 1 / TS 8700 EN 60598-2-5

Seal Type : Resistant To Heat Silicon  
 Diffuser : Tempered Flat Glass  
 Power Factor : 0,95 - 1  
 Body Type : Polymer / GRP, IK 08  
 Box Dimension : 560mmx434mmx185mm

## DIMENSIONS

