



Specifications

- Minimum 70 microns electrostatically powder-coated aluminum injection body and front cover
- Minimum 70 microns electrostatically powder-coated mounting arm, adjustable horizontally (-15°, +15°) and vertically (0°, +15°)
- 4 mm thick tempered glass
- High Power LED with L90B10 >100,000 hours high efficiency factor
- PMMA optical lens options suitable for all road classifications
- High-efficiency driver with constant current output
- One-piece silicone gasket resistant to high and low temperatures
- Stainless steel fastening materials
- Optional NEMA or ZHAGA socket compatible with smart city lighting systems
- Optional 10kV spd surge protective device

Nominal Power	30 W		
Nominal Voltage	220-240 VAC - 50-60 HZ		
Luminous Flux	C	B	A
	3.750 lm*	4.050 lm*	4.500 lm*
Efficiency	125 lm/W	135 lm/W	150 lm/W
Power Factor	≥0,95		
IEC Protection Class	Class I		
Surge Protection	6-10 Kv		
Mounting Diameters	Ø42 mm - Ø60 mm		
Dimensions	675x345x108 mm		
Weight	8,9 kg		

*The given lumen value is valid for 4000K-70CRI. Please contact us for other options.

Options

Light Color and CRI Options	3000 K - CRI 70	37
	3000 K - CRI 80	38
	4000 K - CRI 70	47
	4000 K - CRI 80	48
	6500 K - CRI 70	67
	6500 K - CRI 80	68


System Options	On-Off Std	01
	1-10V Dim	02
	TEDAŞ	06
	DALI	07
	1-10V with Nema Socket	08
	DALI with Zhaga Socket	09

Road Optic Options	S15M5	16
	S14M4	15

Body Colour Options	RAL7016MAT	716
	RAL9005MAT	905
	RAL9016MAT	916

Dimensions

L1	L2	W	H1	H2
576mm	675mm	345mm	82mm	177mm





Order Code



AR	Material Group
LP0	Product Model
C	Lumen Segment
030	Product Power (W)
47	Color and CRI Options
10	Optical Options
01	System Option
716	Body Color Option

AR	-	LP0	-	C	-	030	-	47	-	10	-	01	-	716
----	---	-----	---	---	---	-----	---	----	---	----	---	----	---	-----

S15M5



S14M4



Projects

