





Dimensions

L1	L2	W	H1	H2
423mm	560mm	252mm	70mm	154mm



Order Code

AR	Material Group
SH5	Product Model
C	Lumen Segment
075	Product Power (W)
47	Color and CRI Options
15	Optical Options
01	System Option
716	Body Color Option

AR	-	SH5	-	C	-	075	-	47	-	15	-	01	-	716
----	---	-----	---	---	---	-----	---	----	---	----	---	----	---	-----

Specifications

- Minimum 70 mic. electrostatic powder-coated aluminum injection body
- Minimum 70 mic. electrostatic powder-coated adjustable mounting arm in horizontal (-15°, +15°) and vertical (0°, +15°) directions
- 4 mm thick tempered glass
- L80B10>100,000 hours high-efficiency factor Mid Power LED
- PMMA optical lens with options suitable for all road classes
- High-efficiency driver with constant current output
- One-piece silicone gasket resistant to high and low temperatures
- Stainless steel connection materials
- Optional 10kV surge protector resistant to network fluctuations

Nominal Power	75 W		
Nominal Voltage	220-240 VAC - 50-60 HZ		
Luminous Flux	C	B	A
	9.375 lm*	10.125 lm*	11.250 lm*
Efficiency	125 lm/W	135 lm/W	150 lm/W
Power Factor	≥0,95		
IEC Protection Class	Class I		
Surge Protection	6-10 Kv		
Mounting Diameters	Ø42 mm - Ø60 mm		
Dimensions	560x253x81 mm		
Weight	4,8 kg		

*The given lumen value is valid for 4000K-70CRI. Please contact us for other options.

Options



Light Color and CRI Options	3000 K - CRI 70	37
	3000 K - CRI 80	38
	4000 K - CRI 70	47
	4000 K - CRI 80	48
	6500 K - CRI 70	67
	6500 K - CRI 80	68

System Options	On-Off Std	01
	1-10V Dim	02
	DALI	07
	1-10V with Nema Socket	08
	DALI with Zhaga Socket	09



Road Optic Options	S10M3	11
	S12M4	13
	S13M4	14
	S14M4	15

Body Colour Options	RAL7016MAT	716
	RAL9005MAT	905
	RAL9016MAT	916



S10M3



S12M4



S13M4



S14M4

