




Dimensions

Diameter	W	H1	H2
340mm	290mm	55mm	160mm



Order Code

AR	Material Group
HCO	Product Model
A	Lumen Segment
180	Product Power (W)
47	Color and CRI Options
07	Optical Options
01	System Option
01	Mounting Options

AR - HCO - A - 180 - 47 - 07 - 01 - 01

Specifications

- High-efficiency and durable LED luminaire designed for industrial facilities
- Die-cast aluminum housing with minimum 70 µm electrostatic powder coating
- High-efficiency Mid-Power LEDs with L90B10 > 80,000 hours lifetime
- IP67 PMMA optical lens options suitable for industrial applications
- High-efficiency constant-current IP67 LED driver
- One-piece silicone gasket resistant to high and low temperature conditions
- Stainless steel mounting accessories
- Optional suspended or busbar mounting configurations

Nominal Power	180 W
Nominal Voltage	220-240 VAC - 50-60 HZ
Luminous Flux	A
	26.100 - 28.800 lm
Efficiency	145 - 160lm/W
Power Factor	≥0,95
IEC Protection Class	Class I
Surge Protection	2-4 Kv
Dimensions	340x 160 mm
Weight	3 kg

*The given lumen value is valid for 4000K-70CRI. Please contact us for other options.

Options


Light Color and CRI Options	3000 K - CRI 70	37
	3000 K - CRI 80	38
	4000 K - CRI 70	47
	4000 K - CRI 80	48
	6500 K - CRI 70	67
	6500 K - CRI 80	68

System Options	On-Off Std	01
	1-10V Dim	02
	DALI	07
	Zhaga Soketli DALI	09
	3-Hour Emergency Kit	14
	IN Driver	15


Optical Options	10 Degree	04
	25 Degree	05
	60 Degree	07
	90 Degree	08
	Symmetrical Oval Beam	09

Mounting Options	Cable Tray Mounting	01
	Busbar Mounting	02
	Suspended Mounting	03


10 Degree




25 Degree



60 Degree



90 Degree



Symmetrical Oval Beam

