




## Dimensions

Diameter	W	H1	H2
340mm	290mm	55mm	160mm



## Order Code

AR	Material Group
HCO	Product Model
A	Lumen Segment
200	Product Power (W)
47	Color and CRI Options
07	Optical Options
01	System Option
01	Mounting Options

AR - HLO - A - 200 - 47 - 07 - 01 - 01

## Specifications

- High-efficiency and durable LED luminaire designed for industrial facilities
- Die-cast aluminum housing with minimum 70 µm electrostatic powder coating
- High-efficiency Mid-Power LEDs with L90B10 > 80,000 hours lifetime
- IP67 PMMA optical lens options suitable for industrial applications
- High-efficiency constant-current IP67 LED driver
- One-piece silicone gasket resistant to high and low temperature conditions
- Stainless steel mounting accessories
- Optional suspended or busbar mounting configurations

Nominal Power	200 W
Nominal Voltage	220-240 VAC - 50-60 HZ
Luminous Flux	A 29.000 - 32.000m
Efficiency	145 - 160lm/W
Power Factor	≥0,95
IEC Protection Class	Class I
Surge Protection	2-4 Kv
Dimensions	340x 160 mm
Weight	3 kg

\*The given lumen value is valid for 4000K-70CRI. Please contact us for other options.

## Options


Light Color and CRI Options	3000 K - CRI 70	<b>37</b>
	3000 K - CRI 80	<b>38</b>
	4000 K - CRI 70	<b>47</b>
	4000 K - CRI 80	<b>48</b>
	6500 K - CRI 70	<b>67</b>
	6500 K - CRI 80	<b>68</b>

System Options	On-Off Std	<b>01</b>
	1-10V Dim	<b>02</b>
	DALI	<b>07</b>
	Zhaga Soketli DALI	<b>09</b>
	3-Hour Emergency Kit	<b>14</b>
	IN Driver	<b>15</b>


Optical Options	10 Degree	<b>04</b>
	25 Degree	<b>05</b>
	60 Degree	<b>07</b>
	90 Degree	<b>08</b>
	Symmetrical Oval Beam	<b>09</b>

Mounting Options	Cable Tray Mounting	<b>01</b>
	Busbar Mounting	<b>02</b>
	Suspended Mounting	<b>03</b>


10 Degree




25 Degree



60 Degree



90 Degree



Symmetrical Oval Beam

